

- PORTS**
- 1 - SWEEP + PERMEATE OUTLET
 - 2 - FEED INLET
 - 3 - PRODUCT OUTLET
 - 4 - SWEEP INLET


Cactus® Dryer

NAMEPLATE PLACED ACCORDING TO THIS ORIENTATION.

MAXIMUM OPERATING TEMPERATURE: 150°F
 MAXIMUM OPERATING PRESSURE: FEED/PRODUCT, 1200 PSIG
 SWEEP/PERMEATE, 1000 PSIG
 MATERIAL: 316 STAINLESS STEEL
 WEIGHT (INCLUDING INTERNALS): 108 LBS

DRAWN: KMJ 2/28/03 APPROVE: WAU 2/28/03

THIRD ANGLE
PROJECTION



PRISM® Membranes

PROPRIETARY NOTICE

THIS DOCUMENT, AND THE INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF AIR PRODUCTS PRISM MEMBRANES (APPM) AND MUST BE KEPT CONFIDENTIAL AND NOT DISCLOSED IN WHOLE OR IN PART TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF APPM. APPM AUTHORIZES THE NECESSARY AND REASONABLE USE OF THIS DOCUMENT, AND THE INFORMATION HEREIN, SOLELY FOR THE EVALUATION, INSTALLATION, OPERATION AND MAINTENANCE OF PRISM MEMBRANE SYSTEMS. NO OTHER USE IS AUTHORIZED.

AIR PRODUCTS PRISM Membranes

MODEL HD4020-12-A0-0E

TITLE EXTERNAL DIMENSIONS

MATERIAL: NOTED

NO. REQ'D: 1 SCALE: 1:4 SHEET 1 OF 1

DWG SIZE A DRAWING / PART NO. 2995-50-13 REVISION 1

REV	DESCRIPTION OF CHANGE	BY	DATE	APP
1	06-013 Chg. fiber desig. in model no. Was: C2 Now: I2	KMJ	1/31/06	WAU
ECR				