

## Cactus® Dryer


- | PORTS |                      |
|-------|----------------------|
| 1     | COMPRESSED AIR INLET |
| 2     | DRY AIR PRODUCT      |
| 3     | PERMEATE PORT        |

D	MODEL NO.	CAP COATING	A (MAX)	B	C	E ± 0.06	F	G	H	L ± 0.12	WEIGHT (LBS)
3/8" NPT	PC3010-P1-3A-20	NONE	3.91	3.88	1.38	4.13	3/8" NPT	3.50	1.10	15.25	4.6
	PC3010-D2-3A-20										
	PC3010-D2-3A-50										
1/2" NPT	PC3020-P1-4A-20	SEE NOTE 1.	3.91	3.88	1.38	4.13	3/8" NPT	3.50	12.73	26.88	6.3
	PC3020-D2-4A-20										
	PC3020-D2-4A-50	NONE							27.10	41.25	8.3
	PC3030-P1-4A-20										
	PC3030-D2-4A-20										
	PC3030-D2-4A-50										

MAXIMUM OPERATING TEMPERATURE: 150°F  
 MAXIMUM OPERATING PRESSURE: 300 PSIG  
 MATERIALS: SHELL: HIGH PERFORMANCE ABS  
 END CAPS: 6061 ALUMINUM

NOTE 1: CLEAR ANODIZE PER MIL-A-8625, TYPE 2, CLASS 1.

DRAWN: KMJ 11/11/97 APPROVE: KMJ 11/12/97



## PRISM® Membranes

SERIES PC3010, 3020, 3030

TITLE EXTERNAL DIMENSIONS

MATERIAL: NOTED

NO. REQ'D: 1 SCALE: 1:2.2 SHEET 1 OF 1

DWG SIZE	DRAWING / PART NO.	REVISION
A	2941-22-12	6

PROPRIETARY NOTICE  
 THIS DOCUMENT, AND THE INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF AIR PRODUCTS PRISM MEMBRANES (APPM) AND MUST BE KEPT CONFIDENTIAL AND NOT DISCLOSED IN WHOLE OR IN PART TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF APPM. APPM AUTHORIZES THE NECESSARY AND REASONABLE USE OF THIS DOCUMENT, AND THE INFORMATION HEREIN, SOLELY FOR THE EVALUATION, INSTALLATION, OPERATION AND MAINTENANCE OF PRISM MEMBRANE SYSTEMS. NO OTHER USE IS AUTHORIZED.

REV	ECR	DESCRIPTION OF CHANGE	BY	DATE	APP
6	06-051	Add -P1 and -50 models.	KMJ	6/12/06	WAU
5	06-021	Add model PC3020-D2-4D-20	KMJ	2/3/06	WAU
4	03-073	REVISED ARROW LOCATION	WAU	9/29/03	WAU
3	01-014	LOGO CHANGE	KMJ	6/20/01	WAB
2	00-014	MODEL NUMBERS WERE PPC-45, 410, 415	KMJ	9/25/00	WAU
1	99-019	REV. OPER. PRES. WAS: 200 PSIG NOW: 300 PSIG	KMJ	7/8/99	WAU