



### Cactus® Dryer

MODEL NO.	A (MAX)	C	D	E ± 0.06	F	G	H	L ± 0.12	WEIGHT (LBS)
PC1010-P1-3A-20	2.16	1.13	3/8" NPT	3.13	1/4" NPT	1.66	3.82	11.88	1.3

MAXIMUM OPERATING TEMPERATURE: 150°F  
 MAXIMUM OPERATING PRESSURE: 300 PSIG  
 MATERIALS: SHELL: HIGH PERFORMANCE ABS  
 END CAPS: 6061 ALUMINUM  
 OUTLET FLOW: 2 SCFM



DRAWN: KMJ 10/20/97 APPROVE: WAU 8/3/98

THIRD ANGLE PROJECTION

## PRISM® Membranes

PROPRIETARY NOTICE  
 THIS DOCUMENT, AND THE INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF AIR PRODUCTS PRISM MEMBRANES (APPM) AND MUST BE KEPT CONFIDENTIAL AND NOT DISCLOSED IN WHOLE OR IN PART TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF APPM. APPM AUTHORIZES THE NECESSARY AND REASONABLE USE OF THIS DOCUMENT, AND THE INFORMATION HEREIN, SOLELY FOR THE EVALUATION, INSTALLATION, OPERATION AND MAINTENANCE OF PRISM MEMBRANE SYSTEMS. NO OTHER USE IS AUTHORIZED.



SERIES PC1010

TITLE EXTERNAL DIMENSIONS

MATERIAL: NOTED

NO. REQ'D: 1 | SCALE: 1:2 | SHEET 1 OF 1

DWG SIZE A | DRAWING / PART NO. 2942-11-13 | REVISION 4

4	01-014	LOGO CHANGE	KMJ	6/20/01	WAB
3	00-014	MODEL NUMBER WAS PPC-21	KMJ	9/25/00	WAU
2	99-004	REV. TO "REV 2" SHELL; OMIT "PLUGGED PORT"	KMJ	3/1/99	WAU
1	98-045	REV. PRES. RATING. WAS: 200 NOW: 300	KMJ	11/17/98	WAU
REV	ECR	DESCRIPTION OF CHANGE	BY	DATE	APP