


Cactus® Dryer

NAMEPLATE PLACED ACCORDING TO THIS ORIENTATION.

MAXIMUM OPERATING TEMPERATURE: 150°F
 MAXIMUM OPERATING PRESSURE: FEED/PRODUCT, 1200 PSIG
 SWEEP/PERMEATE, 1000 PSIG
 MATERIAL: 316 STAINLESS STEEL
 WEIGHT (INCLUDING INTERNALS): 172 LBS

DRAWN: KMJ 2/18/99 APPROVE: WAU 2/19/99

THIRD ANGLE
PROJECTION



PRISM® Membranes

PROPRIETARY NOTICE

THIS DOCUMENT, AND THE INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF AIR PRODUCTS PRISM MEMBRANES (APPM) AND MUST BE KEPT CONFIDENTIAL AND NOT DISCLOSED IN WHOLE OR IN PART TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF APPM. APPM AUTHORIZES THE NECESSARY AND REASONABLE USE OF THIS DOCUMENT, AND THE INFORMATION HEREIN, SOLELY FOR THE EVALUATION, INSTALLATION, OPERATION AND MAINTENANCE OF PRISM MEMBRANE SYSTEMS. NO OTHER USE IS AUTHORIZED.

AIR PRODUCTS **PRISM Membranes**

MODEL HD4050-12-A0-0N

TITLE EXTERNAL DIMENSIONS

MATERIAL: NOTED

NO. REQ'D: 1 SCALE: 1:4 SHEET 1 OF 1

| | | |
|----------|--------------------|----------|
| DWG SIZE | DRAWING / PART NO. | REVISION |
| A | 2995-50-05 | 4 |

| REV | ECR | DESCRIPTION OF CHANGE | BY | DATE | APP |
|-----|--------|--|-----|----------|-----|
| 4 | 06-008 | Chg. fiber desig. in model no. Was: C2 Now: I2 | KMJ | 1/31/06 | WAU |
| 3 | 02-085 | SWEEP/PERMEATE PRESSURE RATING 1000 PSIG | WAU | 06/02/02 | WAU |
| 2 | 01-014 | LOGO CHANGE | KMJ | 6/20/01 | WAB |
| 1 | 00-014 | MODEL NUMBER WAS PPC-2500 | KMJ | 9/25/00 | WAU |