



- PORTS**
- 1 - COMPRESSED AIR INLET
  - 2 - DRY AIR PRODUCT
  - 3 - PERMEATE PORT

### Cactus® Dryer

MODEL NO.	CAP COATING	A (MAX)	B	C	D	E ± 0.06	F	G	H	L ± 0.12	WEIGHT (LBS)
PC4030-D2-6A-20 PC4030-D2-6A-50	NONE	4.92	5.55	1.62	3/4" NPT	4.34	1/2" NPT	4.50	26.12	41.14	14.6
PC4030-D2-6D-20	CLEAR ANODIZE (1)										

NOTE (1): CLEAR ANODIZED PER MIL-A-8625, TYPE 2, CLASS 1

MAXIMUM OPERATING TEMPERATURE: 150°F  
 MAXIMUM OPERATING PRESSURE: 300 PSIG  
 MATERIALS: SHELL: HIGH PERFORMANCE ABS  
 END CAPS: 6061-T6 ALUMINUM

DRAWN: KMJ 11/11/97 APPROVE: WAU 11/12/97



SERIES PC4030

### PRISM® Membranes

TITLE EXTERNAL DIMENSIONS

**PROPRIETARY NOTICE**  
 THIS DOCUMENT, AND THE INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF AIR PRODUCTS PRISM MEMBRANES (APPM) AND MUST BE KEPT CONFIDENTIAL AND NOT DISCLOSED IN WHOLE OR IN PART TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF APPM. APPM AUTHORIZES THE NECESSARY AND REASONABLE USE OF THIS DOCUMENT, AND THE INFORMATION HEREIN, SOLELY FOR THE EVALUATION, INSTALLATION, OPERATION AND MAINTENANCE OF PRISM MEMBRANE SYSTEMS. NO OTHER USE IS AUTHORIZED.

MATERIAL: NOTED		
NO. REQ'D: 1	SCALE: 1:3	SHEET 1 OF 1
DWG SIZE	DRAWING / PART NO.	REVISION
A	2958-51-04	6

6	06-054	ADD MODEL PC4030-D2-6A-50	KMJ	6/13/06	WAU
5	06-046	ADD MODEL PC4030-D2-6D-20	KMJ	6/1/06	WAU
4	05-137	Revise per changes to tube ends (add 2nd arrow).	KMJ	8/10/05	WAU
3	05-072	Add flow arrows to tube ends.	KMJ	4/19/05	WAU
2	01-014	LOGO CHANGE	KMJ	6/20/01	WAB
1	00-014	MODEL NUMBER WAS PPC-430	KMJ	9/26/00	WAU
REV	ECR	DESCRIPTION OF CHANGE	BY	DATE	APP