



- PORTS**
- 1 - COMPRESSED AIR INLET
 - 2 - DRY AIR PRODUCT
 - 3 - PERMEATE PORT

Cactus® Dryer

MODEL NO.	A (MAX)	B	C	D	E ± 0.06	F	G	H	L ± 0.12	WEIGHT (LBS)
PC1020-P1-3A-20	2.16	2.10	1.13	3/8" NPT	3.13	1/4" NPT	1.66	16.71	26.00	1.6
PC1020-P1-3A-50										

MAXIMUM OPERATING TEMPERATURE: 150°F
 MAXIMUM OPERATING PRESSURE: 300 PSIG
 MATERIALS: SHELL: HIGH PERFORMANCE ABS
 END CAPS: 6061 ALUMINUM

DRAWN: KMJ 3/23/99 APPROVE: WAU 3/24/99

THIRD ANGLE PROJECTION

AIR PRODUCTS **PRISM Membranes**

SERIES PC1020

TITLE EXTERNAL DIMENSIONS

MATERIAL: NOTED

NO. REQ'D: 1 SCALE: 1:2 SHEET 1 OF 1

DWG SIZE A DRAWING / PART NO. 2942-10-24 REVISION 4

PRISM® Membranes

PROPRIETARY NOTICE

THIS DOCUMENT, AND THE INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF AIR PRODUCTS PRISM MEMBRANES (APPM) AND MUST BE KEPT CONFIDENTIAL AND NOT DISCLOSED IN WHOLE OR IN PART TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF APPM. APPM AUTHORIZES THE NECESSARY AND REASONABLE USE OF THIS DOCUMENT, AND THE INFORMATION HEREIN, SOLELY FOR THE EVALUATION, INSTALLATION, OPERATION AND MAINTENANCE OF PRISM MEMBRANE SYSTEMS. NO OTHER USE IS AUTHORIZED.

REV	ECR	DESCRIPTION OF CHANGE	BY	DATE	APP
4	06-049	Add model PC1020-P1-3A-50	KMJ	6/12/06	WAU
3	03-082	Rev. per chg. to 2942-10-04 r8.	KMJ	10/27/03	WAU
2	01-014	LOGO CHANGE	KMJ	6/20/01	WAB
1	00-014	MODEL NUMBER WAS PPC-22	KMJ	9/25/00	WAU